

Case	Ø 3.05 x 14	DO-15	Ø 6.3 x 21	Ø 55 x 36		Case
High voltage rectifiers Voltage V_{RRM} [V]						High voltage rectifiers Voltage V_{RRM} [V]
Current	20 mA	100 mA	1 A...0.3 A	1.8 A	2.5 A	Current
Fast recovery	3000	DD300				3000
	4000		BV4	BY4 (1.0 A)		4000
	6000	DD600	BV6	BY6 (1.0 A)		6000
	8000			BY8 (0.5 A)	Si-A 3000/1350-2.5	8000
	10000	DD1000				10000
	12000	DD1200		BY12 (0.5 A)		12000
	14000	DD1400				14000
	16000	DD1600		BY16 (0.3 A)		16000
	18000	DD1800				18000
	24000				Si-A 8000/3600-1.8	24000
		Standard recovery				Standard recovery

Case	MiniMelf	DO-35	DO-41	Case	DO-4
Trigger diodes / Diac Voltage V_{RRM} [V]	SOD-80 / DO-213AA plastic case 			Trigger diodes / Diac Voltage V_{RRM} [V]	
	Power dissipation: 150 mW – Peak pulse current: ± 2 A				Power Zener diodes
28...36	BR100/03 LLD	DB3	BR100/03 DO-41	28...36	12.5 W *)
30...34	BR100/031 LLD		BR100/031 DO-41	30...34	*) mounted on cooling fin
35...45	BR100/04 LLD	DB4	BR100/04 DO-41	35...45	*) montiert auf Kühlblech
					ZX3.9 ... ZX200

Case	Sandwich			Case	
Rectifier cells Voltage V_{RRM} [V]				Rectifier cells Voltage V_{RRM} [V]	
Current	3 A	6 A	12 A	Current	
Standard recovery	50	AG3A	AG6A	AG12A	50
	100	AG3B	AG6B	AG12B	100
	200	AG3D	AG6D	AG12D	200
	400	AG3G	AG6G	AG12G	400
	600	AG3J	AG6J	AG12J	600
	800	AG3K	AG6K	AG12K	800
	1000	AG3M	AG6M	AG12M	1000
		A = 5.4 B = 5.0 C = 2.3	A = 5.7 B = 5.5 C = 2.3	A = 6.5 B = 6.8 C = 2.3	
				Standard recovery	